

AJA Mini-Config Release Notes - v2.26.6

Software for Mini-Config 2.26.6

Introduction

Mini-Config v2.26.6 software adds 4K/2K 48/47.95 frame rate support for the 12G-AM and 12G-AMA, as well as minor maintenance fixes to the Hi5-4K-Plus. It is highly recommended that you update the firmware to avoid any potential issues.

Be sure to consult the Installation and Operation Guide (user manual) for detailed information about features and configuration guidelines. The most current documentation can always be found on the [Mini-Config Support Page](#).

Products Supported in This Release

| | | | | |
|-------------|--------------|-----------|--------------|------------|
| 3G-AM | 12G-AMA-R | HA5-4K | Hi5-12G-R-ST | ROI |
| 3G-AMA | 12G-AMA-R-ST | HA5-Fiber | Hi5-12G-TR | ROI-DP |
| 4K2HD | 12G-AMA-T | HA5-Plus | Hi5-3D | ROI-DVI |
| 12G-AM | 12G-AMA-T-ST | HB-R-SDI | Hi5-3G | ROI-HDMI |
| 12G-AM-R | 12G-AMA-TR | HB-T-SDI | Hi5-4K | ROI-SDI |
| 12G-AM-R-ST | 12GM | HD10MD4 | Hi5-4K-Plus | RovoRx-SDI |
| 12G-AM-T | FS-Mini | HDP2 | Hi5-Fiber | UDC |
| 12G-AMA | HA5-12G | HDP3 | Hi5-Plus | V2Analog |
| | HA5-12G-T | Hi5-12G | LUT-box | V2Digital |
| | HA5-12G-T-ST | Hi5-12G-R | OG-3G-AM | |

New Features in v2.26.6

12G-AM and 12G-AMA

- 4K/2K 48/47.95 frame rate support

Fixes, Changes, and Improvements in v2.26.6

12G-AM and 12G-AMA

- Resolves an issue where a 12G-AM and 12G-AMA do not properly detect and report a 1080p level B signal from a Decimator converter or a BMD ATEM consistently.
- Solves a problem where output embedded audio channel status bits may indicate incorrect audio sample rate.
- Fixes a bug where the Mini-Config user interface would report "??" when the input video was 47.95 or 48 frames per sec.

Hi5-4K Plus

- Resolves an issue where the audio is lost when a unit is powered up or the HDMI cable is unplugged and plugged while receiving signal.
- Fixes a bug where the device would report and output a 4K (4096 x 2160) signal even though the unit was receiving a UHD (3840 x 2160) Quad 3G-SDI source.

Installing the Latest Software

Mini-Converters come from the factory with the most current version of firmware pre-installed. To get the latest version of Mini-Config, visit the AJA website support area and select your Mini-Converter from the list:

<https://www.aja.com/category/mini-converters#support>

The Mini-Config software can be found in the Software section of the support page for your Mini-Converter. Previous releases of the AJA Mini-Config software are also available in the Software Archive section for each supported Mini-Converter.

Firmware Upgrade Procedure

The manual available under the support listings for your AJA Mini-Converter describes the firmware update process; please refer to it in order to properly update your firmware. Product manuals are also installed with the software in the /AJA/Mini-Config/Documentation/folder.

Individual product manuals are available online for download from the Mini-Converter section of the AJA website: <http://www.aja.com/support>.

Technical Support

AJA Technical Support is free and available to help you answer questions or resolve issues with any of your AJA products.

To contact AJA Technical Support:

Email: support@aja.com

Phone: +1-530-271-3190

Fax: +1-530-274-9442

Web: <https://www.aja.com/support/contact>

Shipping: 180 Litton Dr. Grass Valley, CA 95945 USA